

SANAN SA-1519



| | |
|----------------|--------------------------|
| * Image Sensor | 1/3" SONY CCD; |
| * Resolution | 420TVL~700TVL(Optional); |
| * Lens | 9-22mm Manual Zoom Lens; |
| * LED | ∅ 8mm×36PCS; |
| * IR Distance | 50m; |
| * Waterproof | IP66; |
| * Bracket | 3 Axis Bracket; |
| * Other | External lens adjusting. |

| Model | SA-1519 | | |
|-----------------------|---|---|---|
| Image Sensor | 1/3" Sony CCD | | |
| TV System | PAL/NTSC | | |
| Effective Pixel | PAL:500(H)×582(V) NTSC:510(H)×492(V) | PAL:752(H)×582(V) NTSC:768(H)×494(V) | PAL:795(H)×596(V) NTSC:811(H)×508(V) |
| Horizontal Resolution | 420TVL | 540TVL | 600TVL |
| Minimal Illumination | 0.1Lux/F1.2 0Lux(IR On) | | 0.001Lux/F1.2 0Lux(IR on) |
| Synchronous System | Internal Synchronization | | |
| S/N Ratio | >48dB | >54dB | |
| Electronic Shutter | 1/50-1/60,000s(PAL) 1/60-1/60,000s(NTSC) | | |
| White Balance | ATW | | |

| | |
|----------------------------|-------------------------|
| BLC | On |
| AGC | Auto |
| Gamma Adjusting | 0.45 |
| Video Output | 1.0Vp-p at 75Ω |
| Lens | 9-22mm Manual Zoom Lens |
| LED | ∅ 8mm×36PCS |
| IR Distance | 50m |
| Power Supply | DC 12V |
| Working Temperature | -10°C~+50°C RH90% MAX |
| Dimension(mm) | 255mm×144mm×152mm |
| Weight(g) | 1050g |